



Data Sheet

MiniLine

with DC 24-28V / 100W

- Mounted and connected in record time, no tools required
- World-wide approvals (UL, EN, CSA, CB Scheme) for industry and office/home
- Tiny: WxHxD = 73 x 75 x 103mm
- Adjustable output voltage up to DC 28V
- 115/230V Auto Select Input
- PULS Overload Design™ (high output overload capability)
- Selectable single/parallel operation (jumper)

◆ Technical Data ML100.100

◆ Input

| | |
|-------------------------------------|--|
| Input voltage | AC 100-120/220-240V (Auto Select), 47...63 Hz (AC 85...132V / AC 184...264V, DC 220...375V N=⊕ and L=⊖) |
| Input current | <2.1A (@ AC 100V _{in} , 100W P _{out}) <1A (@ AC 220V _{in} , 100W P _{out}) |
| External fusing | not required, unit provides internal fuse (T3A15H, not accessible) |
| Transient immunity | Transient resistance acc. to VDE 0160 / W2 (750V/ 1.3 ms), over entire load range |
| Hold-up time (see diagram below) | >40 ms @ AC 230V, 24.5V / 4.2A >20 ms @ AC 196V, 24.5V / 4.2A >20 ms @ AC 100V, 24.5V / 4.2A |

◆ Efficiency, Reliability

| | |
|--------------------|--|
| Efficiency | typ. 90% (AC 230V, 24.5V / 4.2A) (see also diagram below) |
| Losses | typ. 11.4W (AC 230V, 24.5V / 4.2A) |
| MTBF (Reliability) | appr. 500.000 h acc. to Siemensnorm SN 29500 (24.5V / 4.2A, AC 230V, T _{amb} = +40 °C) |

Prior to shipment, every unit undergoes the following tests in order to isolate any defective units which might suffer an early failure:

- Run-in / burn-in (Full load, T_{amb} = +60°C, on/off cycle)
- Functional test (100 %)

◆ Construction, Mechanics, Installation

Robust plastic housing (US Patent No. D442, 923S), fine ventilation grid on three housing sides to keep out small parts (e.g. screws), IP20

Dimensions and weight

- W x H x D 73 mm x 75 mm x 103 mm (+ DIN rail)
Depth incl. terminals: 98 mm (+ DIN rail)
- Weight 360 g

Mounting orientation  (cf. 'Output')

Ventilation/Cooling Normal convection, no fan required

- Free space f. cooling recom'd.: 25 mm on sides with ventilation grid

Easy snap-on mounting onto the DIN-rail (TS35/7,5 or TS35/15).

Unit sits safely and firmly on the rail; no tools required even to remove

Connection by Spring Clamp terminals; uniformly firm hold, vibration-resistant and maintenance-free: 2 terminals per output

Connector size range

- flexible cable 0.3-2.5mm² (28-12 AWG)
- solid cable 0.3-4mm² (28-12 AWG)
Ferrules admissible
- Wire strip length 6mm (0.24in) recommended

Design details – for your advantage:

- All terminals are easy to reach as mounted on the front panel.
- Input and output are strictly apart from each other (input below, output above) and so cannot be mixed up.
- **Mounting and connection do not require any screwdriver**
→ Easy, quick, durable and reliable installation.

◆ Output

| | |
|--------------------------|---|
| Output voltage | DC 24-28V (adj. by front panel potentiometer) • preset 24.5V ± 0.5% @ 4.2A |
| Voltage regulation | stat. <1% V _{out} (Jumper in pos. 'Single Use') stat. <3% V _{out} (Jumper in pos. 'Parallel Use'), dyn. ±1.5% V _{out} over all |
| Ripple/Noise | <50mV _{pp} (20 MHz bandw., 50 Ω measur.) |
| Overvoltage prot. (OVP) | <36V |
| Output noise suppression | EMI values below EN 61000-6-3, even when using long (>2m), unshielded output cables |
| Rated continuous loading | up to 4.2A @ 24.5V / 3.6A @ 28V (convection cooling), depending on built-in orientation, V _{in} and T _{amb} For details see derating diagram below |
| Overload behaviour | PULS Overload Design™ : No switch-off at overload/short-circuit, instead: up to 1.9 · I _{rated} . So you need no oversizing to start awkward loads. |
| Protection | Unit is protected against (also permanent) short-circuit, overload and open-circuit. |
| Derating | depending on built-in orientation; see diagram below |
| Parallel operation | yes (selectable by front panel jumper) |
| Power back immunity | 35V |
| Operating indicator | Green LED |


◆ Environmental Data, EMC, Safety

| | |
|---|---|
| Ambient temperature range (measured 25 mm below unit) | |
| • storage/transport | -25°C ... +85°C |
| • operation | -10°C ... +70°C (for derating see diagram below) |
| Humidity | max. 95% (without condensation) |
| Electromagnetic emissions (EME) | EN 61000-6-3 (includes EN 61000-6-4) Class B (EN 55011, EN 55022) incl. output noise suppression EN 61000-3-2 (PFC) |
| Electromagnetic immunity (EMI) | EN 61000-6-2 (includes EN 61000-6-1) |
| Safe low voltage: | SELV (EN 60950, VDE0100/T.410), PELV (EN 50178) |
| Prot. class/degree: | Class 1 (EN 60950) / IP20 (EN 60529) |


The PSU complies with all major **safety approvals** for EU (EN 60 950, EN 60204-1, EN 50178), USA (UL 60950, E137006, UL508 LISTED, E198865), Canada (CAN/CSA-C22.2 No 60950 [CUR], CAN/CSA-C22.2 No. 14 [CUL]), CB Scheme (IEC 60950).

◆ Diagrams


Output characteristic V_{out}/I_{out} (min.)



Efficiency (@ V_{out} = 24.5V, typ.)



Derating of output power



Hold-up time with ACin (at V_{out} = 24.5V, typ. + min.)

