



UPS - system

Capacitor buffered power supply

manufacturer: J. Schneider Elektrotechnik GmbH

type : C-TEC 2403-05

Art.-No. : NCPA0727G01001



Short description:

The DC- buffer module of the series **C-TEC** works with ultra-capacitors as energy storage inside the housing. These capacitors are charge by a external regulated DC-power supply in normal operation. In case of an interruption of the DC-power supply the energy of the capacitors is released. The load is supplied by the buffer module till it is discharged. The back-up time depends on the state of charge of the capacitors and on the discharge current.

Nominal input voltage	24 V DC -15/+10 %
Min. nominal input voltage for loading operation	23,5 V
Max. nominal input current	3 A
Nominal output voltage (in mains operation)	24 V
Output voltage range (in buffer mode)	23 V DC 2 %
Max. nominal output current	3 A DC
Current limitation	1,05 ... 1,2 x IA nom
efficiency	> 90 %
energy	500 kJ
Back-up time	Depending on load
Protective system	IP20
Storage temperature	- 40 ... 60 °C
Operational temperature	- 40 ... 60 °C
Relative humidity	95 % non-condensing
Max. altitude (without power reduction)	2000 a. s. l.
Fusing input	6A T. internal
Fusing output	3,15 A T (external)
LED- display	operation LED green illuminates at system-voltage p present at terminal UI UE o.k. LED green illuminates at external supply present Uc > LED green illuminates at: Energy in capacitor > 80 % LED green expires at: Energy in capacitor < 30 % LED is blinking slowly (0,8 Hz): during the charge, until 80 % of the energy of the capacitor is reached LED is blinking fast (3,2 Hz): when the capacitor is discharged
Relais -output	Potential free relais - contact, closer 30 V DC / 0,5 A
Norms and regulations	EN 50 178 / EN 60950
connection, in-/ output	Spring type terminals max. 2,5 mm ²
connection, messages	Spring type terminals max. 1 mm ²

Adresse:
Helmholtzstrasse 13
D-77652 Offenburg
Postfach 2327
D-77656 Offenburg

Tel. +49/(0)781/206-0
Fax +49/(0)781/25318
www.j-schneider.de
info@j-schneider.de

Geschäftsführer:

Bettina Schneider Dipl.Betriebswirt (BA)
Rolf Anti Dipl.-Wirt.-Ing.(FH)
Amtsgericht Offenburg HRB 758

G01001D02-140220
Technische Änderungen vorbehalten!



Reg.-Nr. 2750



dimensions	95 x 60 x 125 mm
weight	0,45 kg
UL-license	UL 508

Adresse:
Helmholtzstrasse 13
D-77652 Offenburg
Postfach 2327
D-77656 Offenburg

Tel. +49/(0)781/206-0
Fax +49/(0)781/25318
www.j-schneider.de
info@j-schneider.de

Geschäftsführer:

Bettina Schneider Dipl.Betriebswirt (BA)
Rolf Anti Dipl.-Wirt.-Ing.(FH)
Amtsgericht Offenburg HRB 758

G01001D02-140220
Technische Änderungen vorbehalten!



Reg.-Nr. 2750