



- **Wide range of input options**
- **Convection cooled: No fans**
- **Low profile**
- **Fully encapsulated, ideal for harsh environments**
- **Fully isolated input – output**
- **Over voltage protection**
- **Overload and short circuit protection**
- **Suitable for a wide range of applications**
- **MTBF > 200,000hrs**
- **Specials input / output combinations on request**
- **Battery Charging options: Consult office**

SPECIFICATIONS

DESCRIPTION

The *GB2-180 series DC/DC converter* is a highly integrated DC/DC converter designed for DC/DC conversion. This series is rated at 180W. With various combinations of input and output voltages, the converters are ideal of any standalone operation.

The unit is encapsulated into an aluminium U-channel as the heatsink surface for the converter. Utilising the latest planar magnetic and high integration ceramic technology, the unit has a small footprint.

Input and Output to the unit are screw terminal block. A green LED indicates the presense of output voltage.

The GB2-180 units can withstand high temperature operation. The maximum surface temperature rise of the heatsink would be around 45°C (55°C for 5V model) above ambient. (Direct skin contact with the heatsink surface should be avoided.)

PHYSICAL

Input Voltage	12VDC (10.8 ~ 16) 24VDC (20 ~ 36) 48VDC (36 ~ 72) 110VDC (80 ~ 140) Other voltages on request
Input Protection	By external fuse
Input Current	12V 24A (nominal 15A) Recommend Fuse: 30A 24V 12A (nominal 8A) Recommend Fuse: 15A 48V 6A (nominal 4A) Recommend Fuse: 8A 110V 3A (nominal 2A) Recommend Fuse: 4A
Input Surge Protection	Designed to meet IEC61000-4-4, -5
Efficiency	Model dependent typically 86%

ELECTRICAL

Voltage Accuracy	Voltage setting within 2%
Output Voltage	Refer to table
Output Voltage Adjustment	Fixed Voltage Output
Output Protection	
Current Limiting	constant current with hiccup mode
Thermal Protection	Automatic recovery after over temperature condition subsides: typically 105°C case temp.
Over Voltage Protection	Unit latch off, reset by recycling input after 2minutes
Isolation	Input – Output: 1000vdc, Input – Chassis: 1000vdc, Output – Chassis: 500vdc
Line Regulation	±0.25%
Load Regulation	±0.5%
Output Ripple & Noise	Switching frequency ripple 0.25% of V out High frequency spike (30MHz BW) 0.5% of V out
Operating Temp	-20°C to +55°C at full load Convection cooled
Humidity	5 ~ 95% RH Non Condensing
Shock & Vibration	Fully encapsulated, designed to meet MIL-STD 810E
MTBF	>200khrs
Indicator	Green LED
Terminals	Input and Output pluggable terminal block

GB2-180 Series

DC/DC Single Output: 180 Watts

STANDARD PREFERRED MODEL TABLE

MODELS	Input Voltage	Output V	Output I	Power
GB2-180-1212	12V	12V	15A	180W
GB2-180-1213.8	12V	13.8	13A	180W
GB2-180-1215	12V	15V	12A	180W
GB2-180-1224	12V	24V	7.5A	180W
GB2-180-1248	12V	48V	3.75A	180W
GB2-180-2412	24V	12V	15A	180W
GB2-180-2413.8	24V	13.8	13A	180W
GB2-180-2415	24V	15V	12A	180W
GB2-180-2424	24V	24V	7.5A	180W
GB2-180-2448	24V	48V	3.75A	180W

STANDARD PREFERRED MODEL TABLE

MODELS	Input Voltage	Output V	Output I	Power
GB2-180-4812	48V	12V	15A	180W
GB2-180-4813.8	48V	13.8	13A	180W
GB2-180-4815	48V	15V	12A	180W
GB2-180-4824	48V	24V	7.5A	180W
GB2-180-4848	48V	48V	3.75A	180W
GB2-180-11012	110V	12V	15A	180W
GB2-180-11013.8	110V	13.8	13A	180W
GB2-180-11015	110V	15V	12A	180W
GB2-180-11024	110V	24V	7.5A	180W
GB2-180-11048	110V	48V	3.75A	180W

