

GIW150 SERIES

AC/DC Power Supplies Rugged Industrial 150W



- Rugged industrial quality
- Conduction/convection cooled - no fan
- Full electronic protection
- Field proven design



This rugged, industrial quality AC/DC power supply uses field-proven technology to generate the required output power. It is a mature product with a track record in numerous applications. The input accepts any AC voltage from 95V to 264Vac. Cooling is via baseplate to a heat-sinking surface and by natural convection. Low component count, large design headroom, and the use of components with established reliability result in a high MTBF.

SPECIFICATIONS

Input Voltage

95V to 264Vac $\pm 15\%$
47 - 63Hz
DC-input also available.
Other inputs available on request

Input Protection

Inrush current limiting
Varistor
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Isolation

2250VDC input to chassis
4300VDC input to output
8mm spacing
500VDC output to chassis
(or corresponding to output voltage)

Standards

Designed to meet EN 60950-1 and corresponding UL and CSA standards.
Several versions have formal agency approvals

EMI

EN55022 Class A with margins

Switching Frequency

47 kHz ± 2 kHz

Hold Up Time

Minimum 5ms at full load for 5% drop of output voltage

Output Voltages

12V/12A, 24V/6A; 36V/4.1A;
48V/3A; 72V/2A or 125V/1.2A are standard.
Other outputs on request.
The output is floating, either terminal can be grounded

Redundancy Diode

Not installed
Available as option

Line/Load Regulation

$\pm 1\%$ combined from zero load to full load

Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

Output Ripple/Noise

Less than 1% of output voltage peak to peak or 0.2% RMS of the output voltage (20MHz BW)

Output Overload Protection

Rectangular current limiting with short-circuit protection (hiccup mode)
Thermal shutdown in case of insufficient cooling (self-resetting)

Output Overvoltage Protection

Second regulator loop, completely stable and independent of main regulator loop

Efficiency

Output voltage dependent.
Typically better than 80% at full load

Operating Temperature Range

0°C to 50°C for full specification installed on heat-sinking surface with good air flow
Extended temperature ranges Available on request

Temperature Drift

0.03% per °C over operating temperature range

Cooling

Conduction to customer heat-sink or chassis and natural convection

Environmental Protection

Basic ruggedizing
Full ruggedizing and conformal coating available as an option

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 – 95% non-condensing

MTBF

140,000 hours @ 45°C
Demonstrated MTBF is significantly higher

Indicators

None on standard version

Control Input

None

Alarm Output

Not installed on standard version
Form C output Fail Alarm on request

Package/Dimensions (W x H x L)

F1: 114 x 51 x 201 mm
(4.5" x 2" x 7.9") including terminal block and flanges
Mounting holes are clear

Weight

0.8 kg (1.8 lbs)

Connections

9-pole barrier-type terminal block, with 3/8" spacing

RoHS Compliance

Fully compliant

Terminal Block Pin-out ($\leq 72V$ output)

DC OUTPUT						AC INPUT		
NOT USED	–	+	NOT USED	NOT USED	NOT USED	$\frac{\perp}{\perp}$	PH	N
1	2	3	4	5	6	7	8	9

Terminal Block Pin-out ($\geq 110V$ output)

DC OUTPUT						INPUT		
+	NOT USED	NOT USED	–	NOT USED	NOT USED	GND $\frac{\perp}{\perp}$	PH (+)	N (-)
1	2	3	4	5	6	7	8	9